

Resumen de servicios a habilitar o deshabilitar

Ejecutar

```
chkconfig --list | grep on
```

para ver que servicios están habilitados

En una máquina virtual

- apmd (advanced power manager)
- anacron
- autofs
- avahi-daemon
- firstboot
- haldaemon
- hidd
- iscsi
- iscsid
- kudzu
- lvm2-monitor
- mcstrans
- mdmonitor
- messagebus
- microcode_ctl
- netfs quitar si no usamos nfs
- nfslock
- pcsd
- portmap quitar si no usamos nfs
- readahead_early
- rpcgssd quitar si no usamos nfs
- rpcidmapd quitar si no usamos nfs
- smartd

Si no usamos NFS

```
/sbin/chkconfig --level 0123456 portmap off
/sbin/chkconfig --level 0123456 nfslock off
/sbin/chkconfig --level 0123456 netfs off
/sbin/chkconfig --level 0123456 rpcgssd off
/sbin/chkconfig --level 0123456 rpcidmapd off
/sbin/chkconfig --level 0123456 autofs off
```

Deshabilitamos el correo

```
/sbin/chkconfig --level 0123456 sendmail off
```

Deshabilitamos la cola de impresión

```
/sbin/chkconfig --level 0123456 cups off
```

Otros

```
$ /sbin/chkconfig --level 0123456 xfs off $ /sbin/chkconfig --level 0123456 isdn off $ /sbin/chkconfig --level 0123456 gpm off $ /sbin/chkconfig --level 0123456 pcmcia off
```

Paquete a desinstalar

```
rpm -e nombrepaquete
```

- apmd
- dosfstools
- ..
- ..
- .

Referencias

<http://www.cyberciti.biz/faq/linux-default-services-which-are-enabled-at-boot/>

From:
<https://intrusos.info/> - LCWIKI

Permanent link:
<https://intrusos.info/doku.php?id=linux:servicios&rev=1364384112>

Last update: **2023/01/18 13:55**

