


Auto Registration

El autoregistro es para que al añadir un equipo al zabbix, este automáticamente lo asigne a unas plantillas y grupos según ciertas condiciones. Para crear unas acciones de autoregistro vamos a **Configuration→Actions** y en el desplegable de la derecha **event source** seleccionamos **Auto Registration** y pulsamos el botón **create action**

En la primera pestaña de **Action** rellenaremos el nombre que queramos darle a esta acción y en el campo **New condition**

The screenshot shows the Zabbix interface for creating a new action. The top navigation bar includes Monitoring, Inventory, Reports, Configuration, and Administration. Below that is a secondary navigation bar with Host groups, Templates, Hosts, Maintenance, Actions (which is highlighted), Event correlation, Discovery, and Services. The main area is titled 'Actions' and has tabs for Action and Operations. The 'Action' tab is active. It contains fields for 'Name' (empty), 'Conditions' (empty), and 'New condition'. Under 'New condition', there is a dropdown for 'Host metadata' set to 'like', a dropdown for 'like' with 'linux' selected, and a text input field. A blue 'Add' button is located below these fields. At the bottom, there is an 'Enabled' checkbox checked and two buttons: a blue 'Add' button and a white 'Cancel' button.

creamos la condición “Host Metadata like Linux” y pulsaremos al enlace azul “ **Add** que está en el recuadro de new condition.



The screenshot shows the Zabbix interface for creating a new action, with the 'Operations' tab selected. The 'Name' field contains 'Registrar equipos linux'. The 'Conditions' and 'New condition' sections are identical to the previous screenshot, with the 'Add' link highlighted by a red box. The 'Enabled' checkbox is checked, and the 'Add' and 'Cancel' buttons are at the bottom.

Pulsamos ahora sobre la pestaña **Operations** y añadimos una nueva operación que nos vincule con la plantilla “OS Linux”

ZABBIX Monitoring Inventory Reports Configuration Administration

Host groups Templates Hosts Maintenance Actions Event correlation Discovery Services

Actions

Action Operations

Default subject Auto registration: {HOST.HOST}

Default message Host name: {HOST.HOST}
Host IP: {HOST.IP}
Agent port: {HOST.PORT}

Operations Details Action

Operation details Operation type Link to template

Templates Template OS Linux Select

Add Cancel

Now, if we click the **Add** button to save the action.

Ahora si, pulsamos el botón de **Add** para grabar la acción

The last step would be to configure the remote agents so that the configuration file has two parameters necessary for auto-registration, **ServerActive** and **HostMetadata**. The configuration file would be similar to:

```
Server=xxx.xxx.xxx.xxx #IP privada servidor Zabbix
ServerActive=xxx.xxx.xxx.xxx #IP privada servidor Zabbix
Hostname= nombre del host
HostMetadata=Linux # etiquetas/metadatos para ese equipo
```

From:
<https://intrusos.info/> - LCWIKI

Permanent link:
<https://intrusos.info/doku.php?id=seguridad:monitorizacion:zabbix3:autoregistro&rev=1511351558>

Last update: 2023/01/18 14:39

